



MOLD CURB® PLUS














Regular & Type X

Mold-Water-Resistant Gypsum Wallboard

PABCO® Gypsum
 a division of PABCO® building products, LLC
 PO Box 405
 Newark, CA 94560
 Technical Services: 866-282-9298
 www.pabcogypsum.com

Mold & Water Resistant Core
 Mold & Water Resistant Paper
 PABCO® Gypsum Specification PGS-010
 ASTM specification C 1396



  	<p>Description:</p>	<p>PABCO® MOLD CURB®<i>Plus</i> products have been engineered with a mold and water-resistant chemistry that provides the most enhanced mold-and-water-resistant protection available in gypsum board products. The PABCO® MOLD CURB®<i>Plus</i> core is comprised of a fire-resistant, non-combustible gypsum core that is encased in 100% recycled light blue colored face paper and gray liner paper on the back. The paper facings additionally</p>	<p>are treated for water and mold-resistance, and include FUNGIBLOCK™ antifungal agent from The Dow® Chemical Company to inhibit mold and mildew. The paper facing on the PABCO® MOLD CURB® <i>Plus</i> product affords a surface suitable for decoration. Tapered edges provide a recessed area which allows the taping and filling of joints to create a monolithic wall finish.</p>
  	<p>Primary Uses:</p>	<p>PABCO® MOLD CURB® <i>Plus</i> mold-and-water-resistant gypsum board panels are interior gypsum board panels. This product may be applied in building applications which require direct mechanical attachment to wood or metal wall and ceiling framing, or may attached to existing surfaces using fasteners</p>	<p>or adhesives. PABCO® MOLD CURB®<i>Plus</i> 1/2" thick panels are intended for single layer applications in residential construction. PABCO® MOLD CURB®<i>Plus</i> 5/8" thick type X panels are intended for single or multiple-layer construction in fire-tested assemblies.</p>
   	<p>Limitations:</p>	<p>Direct exposure to excessive or continuous moisture is to be avoided. PABCO® MOLD CURB®<i>Plus</i> should not be used in areas subject to constant and/or excessive moisture, and high humidity, such as a tile backer or plastic liner application in tub and shower surrounds, gang showers, saunas, steam rooms or swimming pool enclosures.</p>	<p>When PABCO® MOLD CURB®<i>Plus</i> is used as wallboard, framing spacing and fastening shall be as per section 4 of GA-216 (see "Applicable Standards..." following page). PABCO® MOLD CURB®<i>Plus</i> shall not be used where it will be exposed to temperatures exceeding 125° F for an extended period of time.</p>
   	<p>Mold & Water Resistance:</p>	<p>PABCO® MOLD CURB®<i>Plus</i> panels are manufactured with a special formulated gypsum core and paper facing, which provide enhanced protection against water-and-mold as compared to untreated gypsum board panels. In independent laboratory tests per ASTM D 3273 (Standard Test Method for Resistance to Growth of Mold on the Resistance Surface of Interior Coatings in an Environmental Chamber), PABCO® MOLD CURB®<i>Plus</i> products achieved a 10 rating, the highest level of performance for this test method. An extended two-year mold resistant</p>	<p>aging study under varying conditions of temperature and humidity also resulted in a score of 10. No material may be classified as mold-proof. Prolonged exposure to moisture can result in the growth of mold on any surface. The use of good design, with proper handling and construction practices, is the most effective and best method to minimize mold. This includes avoiding water exposure during all phases of the project, such as: storage, handling, shipping, and product installation and system maintenance both before and after project completion.</p>

®DOW, FUNGIBLOCK and the DOW DIAMOND LOGO are trademarks of The Dow Chemical Company ("Dow") or an affiliated company of Dow.



Product Data,
Sizes & Types:

Product	UL Core Type	Thickness	Width	Length ^a ft	Weight ^b
MOLD CURB® Plus Regular	NA	1/2"	48"	8', 12'	1.7 lbs/ft ²
MOLD CURB® Plus type X	PG-5W	5/8"	48"	8', 12'	2.3 lbs/ft ²

Packaging: 2 pieces per bundle, face-to-face, and end labeled.
 Edge type: Tapered
 Material Safety Data Sheet: MSDS available at www.pabcogypsum.com, Technical Data

PABCO's type X products are certified by a third-party inspection service and as evidence of this; each panel bears the Underwriters Laboratories, Inc label for fire resistance, surface burning characteristics and non-combustibility.
^a Other lengths may be available on a special order basis. Consult with your local PABCO® representative, or call PABCO® Technical Assistance.
^b Represents approximate weight for design and shipping purposes. A more exact weight may be available for your area; consult with your local PABCO® representative, or call PABCO® Technical Assistance.

Applicable Standards, Codes
& Technical Data:

Manufacturing: ASTM C 1396 - Water Resistant Gypsum Backing Board
 Federal Specification: Federal Specification SS-L-30D T Type VI, Grades X & R*
 Mold Resistance: ASTM D 3273
 Installation: Gypsum Association GA-216; www.gypsum.org
 ASTM C 840; www.astm.org
 Fire-Resistant Assemblies: Gypsum Association, GA-600 Fire Resistance Design Manual
 Underwriters Laboratories, Inc. UL Fire Resistance Directory
 Surface Burning Characteristics: ASTM E 84; Flame Spread 15; Smoke Developed 0
 Non-Combustible: ASTM E 136
 Thermal Resistance "R value": 1/2" = 0.45; 5/8" = 0.48
 PABCO Gypsum: "Construction Guide - Fire & Sound Rated Systems"
 Recycled Content: Refer to PABCO® Sustainable Materials Data Sheet for plant specific details.
 Foil Application: Foil may NOT be applied to the back of Water Resistant Gypsum Backing Board. See section "Limitations" paragraph #4 above.

Please check our website at www.pabcogypsum.com for the latest edition of this specification.
 *The federal specification for gypsum board, SS-L-30d was withdrawn in 1984. It is provided here for informational purposes only.

Fire Resistant Ratings:

Fire Resistance Rated assembly designs are promulgated from tests performed at IAS* certified independent testing laboratories, and these designs include specific materials assembled in a precise configuration. When choosing construction details to achieve specific fire resistance rated requirements, care must be taken to insure that each component of the specified assembly is the proper one specified in the test report, and assembled in accordance with the specific requirements of the assembly.
 *(The International Accreditation Service —IAS— is a non-profit, public benefit corporation and a leading accreditation body in the United States. Internationally recognized, accreditation by IAS makes it easier to market products and services both inside and outside the United States.)

Storage & Handling:

Store all PABCO® gypsum panels flat; do not store on edge as panels are heavy and may fall over causing injury or death. Store in an area that offers protection from adverse weather conditions, condensation, and other forms of moisture. Avoid job site conditions that expose gypsum board to water or moisture. Plastic shipping bags are temporary, and intended for protection during transit only, and must be removed promptly upon arrival. Store gypsum board under protected cover, off the ground with sufficient support to prevent sagging. Exercise proper care to avoid impact, scuffing of the paper faces, undue flexing, and damage to board edges, corners, and ends.

Submittal Approvals:

Job name:	
Contractor:	Date:

Submittal Approvals: Stamps/Signatures

Limited Warranty: PABCO® Building Products, LLC, warrants that on the date the gypsum board is shipped from its manufacturing plant the gypsum board is free from defects in materials and manufacture. NOTWITHSTANDING THE FOREGOING, IT IS THE RESPONSIBILITY OF THE GYPSUM BOARD APPLICATOR TO NOTIFY PABCO BUILDING PRODUCTS, LLC, IN WRITING WITHIN TWENTY FOUR (24) HOURS OF DISCOVERY OF ANY VISIBLY DEFECTIVE GYPSUM BOARD PRIOR TO SUCH VISIBLY DEFECTIVE GYPSUM BOARD BEING APPLIED; FAILURE TO DO SO MAY FURTHER LIMIT OR VOID THE RESPONSIBILITIES OF PABCO BUILDING PRODUCTS, LLC, UNDER THIS WARRANTY. This warranty will remain in place for one year from the date of shipment from the manufacturing plant. THIS EXPRESS WARRANTY IS THE EXCLUSIVE WARRANTY PROVIDED BY PABCO® BUILDING PRODUCTS, LLC, AND SUPERSEDES ANY PRIOR, CONTRARY OR ADDITIONAL REPRESENTATIONS, WHETHER ORAL OR WRITTEN. PABCO® BUILDING PRODUCTS,

LLC, HEREBY DISCLAIMS AND EXCLUDES ALL OTHER WARRANTIES – WHETHER EXPRESS, IMPLIED, OR STATUTORY – INCLUDING ANY WARRANTY OF MERCHANTABILITY, ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, AND ANY IMPLIED WARRANTIES OTHERWISE ARISING FROM COURSE OF DEALING OR USAGE OF TRADE. If the gypsum board fails to conform to the foregoing warranty in Paragraph 1 and such nonconformity is not due to misuse or improper maintenance or storage, Buyer shall notify PABCO® Building Products, LLC, in writing, and within 60 days of discovery, PABCO® Building Products, LLC, shall provide, at its sole and absolute discretion, one of the following: (i) repair or replacement of any nonconforming or defective gypsum wallboard; or (ii) credit or full refund of the purchase price. THIS REMEDY SHALL BE THE EXCLUSIVE AND SOLE REMEDY OF BUYER FOR ANY BREACH OF WARRANTY.

IN NO EVENT SHALL PABCO® BUILDING PRODUCTS, LLC, BE LIABLE FOR ANY INCIDENTAL, SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, WHETHER RESULTING FROM NONDELIVERY OR FROM THE USE, MISUSE, OR INABILITY TO USE THE PRODUCT OR FROM DEFECTS IN THE PRODUCT OR FROM NEGLIGENCE OR OTHER TORT. This exclusion applies regardless of whether such damages are sought for breach of warranty, breach of contract, negligence, or strict liability in tort or under any other legal theory. Trademarks: The following trademarks used herein are owned by Pacific Coast Building Products and licensed to PABCO® Gypsum: PABCO®, PABCORE®, FLAME CURB®, WATER CURB®, MOLD CURB®, Quality to the Core®, and ABUSE CURB™. Note: Products described herein may not be available in all geographic markets. Consult your PABCO® Gypsum sales representative for information.