

Submittal 09 29 00



PABCORE® SHAFTLINER TYPE X MOLD CURB™ PLUS SHAFTLINER TYPE X

“Quality to the Core”®

PABCO® Gypsum
a division of PABCO® building products, LLC
PO Box 405
Newark, CA 94560
Technical Services: 866-282-9298
www.pabcogypsum.com

PABCO® Gypsum Specification PGS-008
ASTM specification C 1396

Description:

PABCORE® SHAFTLINER type X panels are manufactured with a proprietary fire resistant type X core which has been reinforced with glass fibers and other additives to increase its fire-resistance. This core is encased in 100% recycled water-resistant face and back paper, and features a double beveled edge for ease of installation.

PABCORE® SHAFTLINER type X is distinguishable by the **light green coloration of the water-resistant paper facing.**

PABCORE® MOLD CURB™ PLUS SHAFTLINER type X panels are manufactured with the performance criteria described above, however, in addition, the core and paper facings have been chemically treated for enhanced protection to resist water, mold, and mildew. This product is distinguishable by the **light blue coloration of the paper.**

Primary Uses:

PABCORE® SHAFTLINER type X, and PABCORE® MOLD CURB™ PLUS SHAFTLINER type X panels are designed for lining elevator, ventilation, and utility shafts, as well as constructing lightweight sound attenuation fire-resistant cavity shaft walls, and area separation fire walls in multifamily dwellings such as townhouses, condominiums, and apartments.

These panels are key components in PABCO® Shaftwall Systems utilizing C-H, C-T Studs or H-Studs. PABCO® Shaftwall Systems are easy to erect, achieving fire-resistance ratings of one and two hours. Both solid and cavity-type area separation walls provide Sound Transmission Class (STC) ratings that exceed model building code requirements with designs that achieve STC ratings in excess of 60.

These area separation fire wall assemblies are light weight, weighing no more than 10 lbs/ft² when constructed. As a result, the need for costly footings or foundation modifications are often eliminated. Due to the relatively light weight panels, they can be installed up to four (4) stories in height.

When used as an area separation wall, the system must be:

- Continuous from the foundation to the underside of the protected roof sheathing or continue through the roof to form a parapet.
- Designed to allow for collapse of the construction on the side of the wall exposed to fire without collapse of the area separation fire wall.

Limitations:

- Shaftwall/Stairwell systems are designed as nonload bearing. (NLB)
 - Do not install in areas which will be adjacent to occupancies of unusually high moisture conditions.
 - Where penetrations occur in the assembly, additional reinforcement at corners may be required to distribute stress; approved flexible sealant/caulking may be required to seal around some penetrations.
 - Through penetrations are not allowed in area separation fire walls that are designed to collapse on the fire side.
 - Not recommended for use as an unlined HVAC supply shaft or duct.
 - Limiting heights and deflection criteria must be based upon the metal stud manufacturer's recommendations.
-

Mold & Mildew Resistance:

PABCORE® MOLD CURB™ PLUS SHAFTLINER type X panels additionally provide protection against water, mold, and mildew from the paper facings and the gypsum core as compared to untreated gypsum board panels. In independent laboratory tests per ASTM D 3273 (Standard Test Method for Resistance to Growth of Mold on the Resistance Surface of Interior Coatings in an Environmental Chamber), PABCO® MOLD CURB™ PLUS products achieved a 10 rating, the highest level of performance for this test method.

No material may be classified as mold-proof. Prolonged exposure to moisture can result in the growth of mold or mildew on any surface. The use of good design, with proper handling and construction practices, is the most effective and best method to minimize mold and mildew. This includes avoiding water exposure during all phases of the project, such as: storage, handling, shipping, and product installation and system maintenance both before and after project completion.

Application:

PABCORE® SHAFTLINER type X and PABCORE® MOLD CURB™ PLUS SHAFTLINER type X panels may be used in one and two-hour shaftwall systems, one and two-hour horizontal corridor ceiling systems and two-hour Area Separation Walls. See the PABCO® Gypsum Shaftwall Systems brochure for details.

Product Data, Sizes and Types:

UL Core Type	Thickness	Width	Length ¹	Edge	Weight ²
PG-10	1 inch	24 inches	8, 9, 10 & 12 ft.	Double beveled	4.4 lbs/ft ²

PABCORE® SHAFTLINER products are certified by a third-party inspection service. Each panel bears the UNDERWRITERS LABORATORIES, Inc. label to indicate CERTIFICATION of fire resistance, surface burning characteristics, and non-combustibility.

¹ Other lengths may be available on a special order basis. Consult with your local PABCO® representative, or call PABCO® Technical Assistance.

² Represents approximate weight for design and shipping purposes. A more exact weight may be available for your area; consult with your local PABCO® representative, or call PABCO® Technical Assistance.

Applicable Standards, Codes & Technical Data:

Manufacturing:	ASTM C 1396
Federal Specification:	SS-L-30d Type IV, Grade X *
Mold Resistance:	ASTM D3273
Installation:	Gypsum Association GA-216, www.gypsum.org ASTM C 840, www.astm.org
Fire-Resistant Assemblies:	Gypsum Association GA-600 Fire Resistance Design Manual Underwriters Laboratories, Inc. UL Fire Resistance Directory
Non-combustible:	ASTM E 136
Surface Burning:	ASTM E 84; Flame Spread 15, Smoke Developed 0
R Value:	Thermal Resistance = 0.83
Recycled Content:	Refer to PABCO® Sustainable Materials Data Sheet for plant specific details.
Material Safety Data Sheet:	MSDS available at www.pabco gypsum.com , Technical Data. Please check our website at www.pabco gypsum.com for the latest edition of this specification. <i>*The federal specification for gypsum board, SS-L-30d was withdrawn in 1984. It is provided here for informational purposes only.</i>

Storage & Handling:

Store all PABCO® gypsum panels flat; do not store on edge as panels are heavy and may fall over causing injury or death. Store in an area that offers protection from adverse weather conditions, condensation, and other forms of moisture. Avoid job site conditions that expose gypsum board to water or moisture. Plastic shipping bags are temporary, and intended for protection during transit only, and must be removed promptly upon arrival. Store gypsum board under protected cover, off the ground with sufficient support to prevent sagging. Exercise proper care to avoid impact, scuffing of the paper faces, undue flexing, and damage to board edges, corners, and ends.

Submittal Approvals:

Job Name:	
Contractor	Date:

Limited Warranty: Pabco Building Products, LLC, warrants that on the date the gypsum wallboard is shipped, the gypsum wallboard will meet ASTM C-1396 and will be free from defects in material and manufacture. THIS EXPRESS WARRANTY IS THE EXCLUSIVE WARRANTY PROVIDED BY PABCO BUILDING PRODUCTS, LLC, AND SUPERSEDES ANY PRIOR, CONTRARY OR ADDITIONAL REPRESENTATIONS, WHETHER ORAL OR WRITTEN. PABCO BUILDING PRODUCTS, LLC, HEREBY DISCLAIMS AND EXCLUDES ALL OTHER WARRANTIES – WHETHER EXPRESS, IMPLIED, OR STATUTORY – INCLUDING ANY WARRANTY OF MERCHANTABILITY, ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, AND ANY IMPLIED WARRANTIES OTHERWISE ARISING FROM COURSE OF DEALING OR USAGE OF TRADE.

If the gypsum wallboard fails to conform to the foregoing warranty in Paragraph 1 and such nonconformity is not due to misuse or improper maintenance or storage, Buyer shall notify Pabco Building Products, LLC, in writing, and within a reasonable time, Pabco Building Products, LLC, shall provide, at its sole and absolute discretion, one of the following: (i) repair or replacement of any nonconforming or defective gypsum wallboard; or (ii) credit or full refund of the purchase price. THIS REMEDY SHALL BE THE EXCLUSIVE AND SOLE REMEDY OF BUYER FOR ANY BREACH OF WARRANTY.

IN NO EVENT SHALL PABCO BUILDING PRODUCTS, LLC, BE LIABLE FOR ANY INCIDENTAL, SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, WHETHER RESULTING FROM NONDELIVERY OR FROM THE USE, MISUSE, OR INABILITY TO USE THE PRODUCT OF FROM DEFECTS IN THE PRODUCT OR FROM ACME'S OWN NEGLIGENCE OR OTHER TORT. This exclusion applies regardless of whether such damages are sought for breach of warranty, breach of contract, negligence, or strict liability in tort or under any other legal theory.

Trademarks: The following trademarks used herein are owned by Pacific Coast Building Products and licensed to PABCO® Gypsum: PABCO®, PABCORE®, FLAME CURB®, WATER CURB®, MOLD CURB™, Quality to the Core®.

Note: Products described herein may not be available in all geographic markets. Consult your PABCO Gypsum sales representative for information.